

Kit composition



Carrying case
340 X 270 X 83 mm
Code MI136



Devices spec



PicoScope 2205A
2 Channel, 25 MHz, 200 MS/s, 16 Ks
Code PP966



20 A / 60 A DC (low amps) current clamp
1 mV/10 mA (100 mV = 1 A)
— use this for testing currents up to 20 A.
1 mV/100 mA (10 mV = 1 A)
— use this for testing current up to 60 A.
Code TA018



Premium Test Lead: BNC to 4 mm, 3 m
Code TA125



Piercing Clip
Code TA007A



**Large Dolphin/
Gator Clips Battery**
Code TA158

ENERGIA Alliance GMBH.

Tel: +49 (0)89 208039 226
Adres: Leopoldstrasse 244, 80807 München/
Germany Mail: info@energiainalliance.com
Web: www.energiainitaly.com

Composizione del kit



Valigetta
340 X 270 X 83 mm
Codice MI136



Specifiche dei dispositivi



PicoScope 2205A
2 Canali, 25 MHz, 200 MS/s, 16 Ks
Codice PP966



20 A / 60 A DC (basso amperaggio) pinza di corrente
1 mV/10 mA (100 mV = 1 A)
— use this for testing currents up to 20 A.
1 mV/100 mA (10 mV = 1 A)
— use this for testing current up to 60 A.
Codice TA018



Sonda di test Premium: BNC da 4 mm, 3 m
Codice TA125



Clip rubacorrente
Codice TA007A



Clip cocodrillo grande da batteria
Codice TA005